

*The Signs
you want
when you
need them!*

Head Office
11310 - 97 Avenue
Grande Prairie, AB
T8V 4Y6



SUBSTRATE LIST

COROPLAST

Corrugated plastic, generally for inside use. Outside use with minimal exposure 1 - 2 years. Standard thickness is 4.0 mm (also available in thickness ranging from 4 mm to 10 mm). Available in several colour options.

STYRENE

Interior lightweight plastic that is multi-use. Comes in a variety of thicknesses. Our standard stock is .020" and .040". Perfect for tags.

POLYBLEND

.055 Polyblend is a UV stabilized polyethylene sheet that has been corona treated on both sides for increased longevity. Outside/Inside use, not meant to be used in extremely cold temperatures.

SINTRA

Expanded smooth surface PVC sheet, excellent for interior use. Standard thickness is 3 mm and 6 mm. Available in a variety of colours.

INTACEL

White expanded PVC sheet, can be routered, glued, drilled and painted. Inside use. Outside use with minimal exposure, will warp in sun if large in size. Used for sandwich boards. Standard thickness is 3/8"

MAGNETIC SHEETING

Vehicle Grade magnetic sheeting with a white semi-gloss surface. .030" thickness.

PLEXI & LEXAN

Plexiglass is a transparent plastic intended as a replacement for glass. Lexan is a highly durable polycarbonate resin thermoplastic excellent for backlit signage. Comes in a variety of thickness and color options. Excellent for outdoor long term usage.

GATORFOAM

A structural panel of polystyrene foam core and wood fibre veneer. Excellent for outdoor applications but MUST be protected from UV degradation by painting.

ULTRABOARD

Extruded polystyrene foam core with .015" high impact polystyrene faces. Frequently used for 3 dimensional router cut signage. Interior usage only.

DIBOND

Dibond material is an 3 mm aluminum composite material made of two light weight sheets of .010" aluminum with a thermoplastic core. Excellent for long-term exterior use. Available in a variety of colours.

ALUMINUM

.080 Standard traffic spec metal covered in either engineering grade, diamond grade, or high-intensity reflective vinyl. Outdoor use.

CREZONE

Machine painted plywood, good for printing on one side. 3/8 standard thickness. Exterior use.

***Give us a call and our sales rep can bring some samples of these substrates to your office.
Custom materials are available, this is only a list of our most commonly used materials.
Feel free to inquire if you have any questions.***

25
YEARS
INDEPENDENTLY OWNED & OPERATED

p: 780.538.3338
f: 780.538.2356
signs@sosgraphics.ca